

IN THE SPECIFICATION

Amendment to the specification

On page 2, line 22, please insert after the word "base":

--from 130 degrees - 50 degrees and uncouples the base at 180 degrees --.

DISCLOSURE OF THE INVENTION

The system is based on the principle that an equal and opposite force is produced when an unbalanced weight is rotated. This force or motion causes the system to rotate about its center of mass and thus traverse a circular path in space. Two such weights are mounted on a carriage plate and are rotated in synchrony in opposite directions by two drive motors in order to cancel lateral forces. The carriage plate that carries the counter-rotating weights is mounted on a linear slide, so when the weights rotate, the carriage plate moves back and forth on the slide. The distance that this carriage moves on the linear slide is determined by the ratio of the weight of the weights to the weight of the slide, and the length of the coupling arms of the weights. This mechanism it will only reciprocate back and forth on the linear slide as the weights rotate, it is not yet a propulsion system. In order for this mechanism to perform as a propulsion system, the reciprocating motion of the carriage on the slide has to be selectively timed and coupled to the base of the unit that the slide is mounted on. The slide is mounted on the base and this base can also be the vehicle that is moved forward. In order to move forward, the base requires an additional element or device that periodically couples the motion of the carriage to the base and thus moves the base. The device that is used to accomplish this is an electric solenoid, which is mounted to the base. When the solenoid is activated the solenoid plunger engages the slide during a pre-determined point on its travel on the slide and thus couples the slide solidly to the base from 130 degrees - 50 degrees and uncouples the base at 180 degrees. Since the slide is in motion this motion is coupled to the base. The coupling and uncoupling points and timing are crucial to the proper operation of this device. The system starts out with zero momentum or no motion forward. After one complete cycle the propulsion system has moved forward some amount, for example one inch. The base is again stopped with no forward momentum. Then the weights are again in their initial position and are ready to repeat the cycle. The base of this system is again stopped with zero forward momentum.

On page 3, lines 6 and 7, after the word "at" please insert --50 degrees to 130 degrees -- please delete "90+/- 40 degrees" and please delete after 180 "+/-20".

On page 3, line 21, please delete "270" and insert therefore --180--.

zero forward momentum. The weights continue to rotate and the carriage continues its back and forth motion on the slide. This is true of the first mode of operation. In the second mode of operation an increment of velocity is added to the device that the propulsion system is mounted on during each cycle. Let us examine the operation of the basic motive mechanism. One complete cycle of the mode 1 operation consists of one complete rotation of the weights. Figure 10 is the actual representation of the paths of the weights. The power or forward cycle begins at 50 degrees to 130 degrees ~~90+/- 40 degrees~~ and ends at ~~180+/-20~~ degrees. The power cycle may start earlier, depending on the velocity of the weights and their kinetic energy in relation to the kinetic energy of the slide. During this time the carriage is locked to the base, so if the weight goes forward the carriage and base move in the opposite direction. Since the carriage and base are locked together they constitute one mass. The weights constitute the other mass. The equal and opposite momentum of these two masses cancel at 180 degrees and the base stops in space. The weights however continue to rotate. The carriage and weights are now only acting against each other, so the motion of each is proportional to the other. There is a non-symmetric condition created when the solenoid combines the weights of the base and the carriage. Symmetric rotation is no longer true. The weights have constant rotary motion in relation to the carriage and certain inertia. The carriage however must stop, since it is traveling back and forth. Notice the distance that the carriage has traveled while the weight traveled from 180 degrees to 270 degrees. This distance traveled by the carriage from 270 to 360 degree travel by the weights is close or the same as in the previous segment of travel from 180 to 270 degrees. At 180 ~~270~~ degrees the carriage is at its most rearward travel and must reverse direction. This means that the carriage at that point has no momentum. The weights are at 360 degrees and were constrained to proportional travel during the previous segments. At 360 degrees the weight is acting against the carriage (at 360 degrees the carriage is stopped) that now has no kinetic energy. This enables the weights, due to their forward momentum, to take a more tangential path to their normal orbital path. In other words, the weights are able to drag the carriage along due to their kinetic energy and momentum. Notice that the distance that the carriage traveled from 360 degrees back to 90 degrees is twice that of the previous segment. This disproportionate travel of the carriage from

360 to 90 degrees enables the propulsion system to reset itself to initial conditions and repeat the next cycle.

On page 4, line 4 through 11, please delete "Notice that the carriage and the weights, during part of the rotation segment from 360 to 90 degrees, are traveling in the same forward direction. If you have two coupled masses simultaneously traveling in the same direction you can couple some of this kinetic energy to a third outside body. There are several ways that his can be accomplished during this propulsion system. During the segment that the carriage and weights are traveling in the same direction you can couple some of this energy directly to a third boy by attaching a coupling mechanism to the slide that can be engaged to the third body and thus accelerate the third body. Another" and insert therefore --The--

On page 4, line 22 please delete "other 270" and insert therefore --remaining--.

On page 4, line 25, please delete "90" and insert therefore --50 degrees to 130 --.

The second mode of operation (this mode enables the system to accelerate additively each time it is engaged) also takes advantage of this new non-symmetric behavior. ~~Notice that the carriage and the weights, during part of the rotation segment from 360 to 90 degrees, are traveling in the same forward direction. If you have two coupled masses simultaneously traveling in the same direction you can couple some of this kinetic energy to a third outside body. There are several ways that this can be accomplished during this propulsion system. During the segment that the carriage and weights are traveling in the same direction you can couple some of this energy directly to a third body by attaching a coupling mechanism to the slide that can be engaged to the third body and thus accelerate the third body. Another~~ The method to accomplish the mode 2 operation is to couple the slide to the base and also couple the base to the body to be accelerated. The degree of coupling to the third body can be varied. The engagement of the second mode of operation may cause the carriage and the weights to change their position in relation to the base. The consequence is that you run out of slide. In other words, the carriage and weights are on the rear position of the slide. This action may require engaging the mode one operation and or repositioning the carriage and weight assembly by a servo mechanism that re-synchronizes the parts to their proper position in relation to the base, and their position on the third body that is being accelerated and is now in motion.

One complete cycle of the mode 1 operation consists of one complete rotation; of the weights. The propulsion unit only moves forward during 90 degrees of rotation, the remaining ~~other 270~~ degrees of rotation are used to reset the system back to initial conditions. Figure 10 is the actual representation of the paths of the weights in reference to the base. The power or forward cycle begins at 50 degrees to 130 90 degrees and ends at 180 degrees. During this time the carriage is locked to the base, so if the weights go forward and the carriage and base move in the opposite direction, since the carriage and base are locked together they constitute one mass. The weights constitute the other mass. The equal and opposite momentum of these two masses cancel at 180 degrees and the base stops in space. The carriage is uncoupled from the base at this point. The weights however continue to rotate. The carriage and weights are now only acting against each other, so the motion of each is proportional to the other.

On page 5, line 11, after the word "At" please delete "270" and insert therefore --180--.

On page 5, line 22, please delete "have".

On page 5, lines 24 through 29, please delete "The second mode of operation also takes advantage of this new behavior. Notice that the carriage and the weights, during part of the rotation segment from 360 to 90 degrees, are traveling in the same forward direction. If you have two coupled masses simultaneously traveling in the same direction you can couple some of this kinetic energy to a third outside body. This energy coupling to a third body makes the mode 2 operation possible. The mode 2 operation enables this energy to accelerate the third body, which could be a spacecraft. By" and insert therefore --The second mode of operation also utilizes this behavior. The second mode of operation enables the acceleration of the third body, which could be a spacecraft. By--.

There is a non-symmetric condition created when the solenoid combines the weights of the base and the carriage because the ratio of the interacting masses has changed and also the center of mass, since the masses interacting are now different. The weights have a constant rotary motion, so the weights have a certain fixed inertia. The carriage however must stop momentarily at 180 and 360 degrees since it is traveling back and forth, therefore the carriage has variable inertia. Notice the distance that the carriage has traveled while the weight traveled from 180 degrees to 270 degrees. This distance traveled by the carriage from 270 to 360 degree travel by the weights is close or the same as in the previous segment of travel from 180 to 270 degrees. At 180 ~~270~~ degrees the carriage is at its most rearward travel and must reverse direction. This means that the carriage at that point has no momentum. The weights are at 360 degrees and were constrained to proportional travel during the previous segments. At 360 degrees the weights are acting against the carriage that now has no kinetic energy. This frees or enables the weights to take a more tangential path to their normal orbital paths. In other words, the weights are able to drag the carriage along due to their kinetic energy and momentum. Notice that the distance that the carriage traveled from 360 degrees back to 90 degrees is twice that of the previous segment.

This mechanism enables the propulsion system to reset itself to initial conditions and repeat the next cycle. If the speed of rotation of the weights is increased the kinetic energy of the weights is also increased. This enables the carriage to reach its initial condition before the weights ~~have~~ reach 90 degrees. This makes it possible to increase the size of the power cycle.

~~The second mode of operation also takes advantage of this new behavior. Notice that the carriage and the weights, during part of the rotation segment from 360 to 90 degrees are traveling in the same forward direction. If you have two coupled mass simultaneously traveling in the same direction you can couple some of this kinetic energy to a third outside body. This energy coupling to a third body makes the mode 2 operation possible. The mode 2 operation enables this energy a accelerate of the third body, which could be a spacecraft. By~~

This second mode of operation also utilizes this behavior. The second mode of operation enables the acceleration of the third body, which could be a spacecraft. By

proper timing of the coupling to the third body this body can be accelerated an additional increment each time that this is done. These increases in acceleration are additive. /

On page 6, lines 2 through 7, please delete "Another method of coupling the energy or momentum to a third body is to couple the forward momentum of the slide and weights to the base. This can be done by capturing and braking their momentum by a solenoid or other device that is coupled to the base. This coupling means transfers the momentum of the weights and the slide into forward momentum of the base."

~~Another method of coupling the energy or momentum to a third body is to couple the forward momentum of the slide and weights to the base. This can be done by capturing and braking their momentum by a solenoid or other device that is coupled to the base. This coupling means transfers the momentum of the weights and the slide into forward momentum of the base.~~

On page 9, line 15, please delete "20" and insert therefore --2--.

On page 9, lines 26 and 27, please delete "Weights are at the 90 degree position on FIGURE 12." And delete "90" and insert therefore --45--.

In whichever design configuration is utilized the motors 40 and 44 are operated by a power source 46. This power source may consist of a rechargeable battery 48 as shown in FIGURE 6, a nuclear battery 50, as shown in FIGURE 7; an array of photovoltaic cells 52, as shown in FIGURE 8; or a combination of the above power sources or a fuel burning combustion engine 54 as shown in FIGURE 9. The motor 40 can also be mounted on the base 14 and a flexible or movable shaft can couple energy to the weights 42 via gears 94, as shown in FIGURE 14. The propulsion unit, as shown in Figure 2 ~~20~~ can be rotated on the payload platform 90, as shown in Figure 15 to reverse the direction of travel of the payload platform.

FIGURE 12 will be used to explain the operation of the mode 1 operation. Remember that the forward or power cycle of the mode 1 operation is from 90-180 degrees, and the rest of the rotation of the weights are the reset to initial conditions, as shown in FIGURES 10 and 17. The mode 1 weight paths, are shown in FIGURE 10, and in conjunction with FIGURE 12, explain the operating sequence of mode 1. The weights 42 are shown in Fig. 12 to be about the 235 degree position. ~~Weights are at the 90 degree position on FIGURE 12.~~ The weights are shown in the 45 ~~90~~ degree position in a means 96 to rotate or reverse the action of the propulsion system on the payload platform 90.

On page 11, lines 24 and 25, please delete "There are several different methods to operate the propulsion system 12 in the second mode."

If the reference position of the carriage 30 is lost in relation to the base 14 due to friction or misalignment over time a servo mechanism 56, as shown on FIGURE 2, re-positions the carriage 30 on the slide base 20 so the unit will not run into the stops 64 or 84. The mode 2 operation can be best understood with the help of FIGURES 3, 10, 12 and 17. ~~There are several different methods to operate the propulsion system 12 in the second mode.~~ The second mode of operation utilizes all of the operations of mode 1. The mode 2 operating system enables a payload platform, as shown in FIGURE 15, to be accelerated an increment of velocity during each cycle in which the mode 2 components of the system are engaged. These incremental acceleration steps are additive and thus the payload platform 90 can reach great velocities. FIGURE 15 shows a means 96 to rotate or reverse the action of the propulsion system on the payload platform 90.

On page 12, lines 3 through 10. Please delete "Another method of accelerating the payload platform 90 is possible. During part of the rotational cycle the weights 42 and the carriage 30 travel in the same direction from 360 degrees to approximately 45 degrees of the rotation of the weights 42, as shown in FIGURE 10. Notice the disproportionate travel of the carriage while the weights 42 rotate from about 360 degrees to 90 degrees, as shown in FIGURES 10 and 17. During the portion of this travel, as shown in FIGURE 4, a weight grabbing means 26 is activated by a stopping means solenoid 25. The proper timing for this action is determined by a weight position sensor 73. This action couples the slide 30 and the" and insert therefore --The method of accelerating the payload platform 90 is as follows. The proper timing is determined by a weight position sensor 72. This action couples the carriage 30 and the--.

On page 12, line 12, please delete "can be" and insert therefore --is--.

~~Another method of accelerating the payload platform 90 is possible. During part of the rotational cycle the weights 42 and the carriage 30 travel in the same direction from 360 degrees to approximately 45 degrees of the rotation of the weights 42, as shown in FIGURE 10. Notice the disproportionate travel of the carriage while the weights 42 rotate from about 360 degrees to 90 degrees, as shown in FIGURES 10 and 17. During the portion of this travel, as shown in FIGURE 4, a weight grabbing means 26 is activated by a stopping means solenoid 25. The proper timing for this action is determined by a weight position sensor 73. This action couples the slide 30 and the~~

The method of accelerating the payload platform 90 is as follows. The proper timing is determined by a weight position sensor 72. This action couples the carriage 30 and the weights to the base 14. The momentum of the carriage 30 and the weights 42 are thus transferred to the base 14 and accelerate the base. The base is can be coupled to the payload platform during this time by a solenoid 104 that is fixed to the payload 90, thus resulting in the acceleration of the payload platform 90.

No additional fee is deemed necessary at this time.

Respectfully submitted,

A handwritten signature in dark ink, appearing to read "A. O. Cota", with a stylized flourish at the end.

Albert O. Cota
Agent of Record
Registration No. 29,291

(818) 368-4332